

# 5GHz 300Mbps Hi-Power Outdoor Wireless WISP CPE / ROUTER

## WIS-Q5300




## Product Overview

WIS-Q5300 is a Hi-Power outdoor wireless access point and CPE based on 802.11a/n technology. It is high performance, cost-effective and dedicated to long distance wireless network solutions. Featuring the revolutionary power boost technology in hardware design and 16dBi directional dual-polarized antenna, WIS-Q5300 is specialized designed for rural Internet access, long distance wireless data transmission, wireless coverage extension and other industrial wireless solutions.

## Features and Benefits

- WiD TDMA greatly improves the network scalability in throughput and latency
- Gigabit LAN port helps get maximum performance of Wi-Fi
- Multi-operation modes support WISP Mode/Router/Access Point/Station
- 16dBi dual-polarized antenna to build long distance wireless connection
- High output transmission power and receive sensitivity optimized
- Passive POE(24VDC) for flexible deployment
- Supports site survey and RSSI signal LEDs
- IP65 outdoor Weather-proof housing selectable
- OEM/ODM, customized enclosure and software available

## Network Example



*The WIS-Q5300 as clients in PtMP WISP connection for home and enterprise users.*

## Specification

---

### > Radio

- 802.11a/n radio (Atheros 600MHz)
  - Speed up to 300 Mbps
  - Frequency Range: 5.150-5.250GHz  
5.250-5.350GHz (Support DFS)  
5.470-5.725GHz (Support DFS)  
5.725-5.825GHz
  - Tx Power up to 27dBm
  - Rx Sensitivity 300M: -74dBm@10% PER  
54M: -78dBm@10% PER  
1M: -98dBm@10% PER
- 

### > Antenna

- 16dBi dual-polarized directional antenna
  - Beamwidth(HPBW) Horizontal: 45°, Vertical: 14°
  - Open space up to 1~10km (dependent)
- 

### >Physical Parameters

- Dimension: 180\*95\*44mm
  - Weight: 0.27kg
  - Enclosure: Weatherproof Plastic
  - ESD Protection: 15kV
  - Lightning Protection: 4kV
  - Working Temp: -40 ~ 65°C
  - Storage Temp: -40 ~85°C
  - Working Humidity: 10%~95% non-condensing
- 

### >Security

- Integrated Firewall
  - WPA/WPA2;WPA-PSK/WPA2-PSK (AES/TKIP)  
Encryption; 64/128-bit WEP;
- 

### > Interfaces

- 1x 10/100/1000 Base-T Ethernet  
(RJ45 with Passive PoE)
  - Reset
- 

### > Power

- 24VDC, 0.75A
  - Power Consumption: 6W
- 

### >LED

- Power:On/Off
  - LAN:On/Off/Flashing
  - WLAN:On/Off/Flashing
  - RSSI Signal: 1,2,3
- 

### >Warranty

- 1 Year
- 

### >Certification

- CE, RoHS
- 

### >Package content

- WIS-Q5300
  - Quick Setup Guide
  - Power Adapter with Passive PoE
  - RJ-45 Ethernet Cable
  - Mounting kits
-