

WCAP-AX-Plus

Wi-Fi 6 Indoor Access Point







Wi-Fi 6 Indoor Access Point

Model: WCAP-AX-Plus

The WCAP-AX-Plus Access Point is one of the wireless products fully developed by WIS Networks. The device supports 802.3at PoE In power supply. With concurrent 2.4GHz and 5GHz, the AP supports dual-band dual-stream MIMO technology, providing 574Mbps at 2.4G, and 2402Mbps at 5G.

WIS Networks Ltd.

info@wisnetworks.com www.wisnetworks.com



Integrated Fat/Fit AP + AC Architecture

WisCloud Controller is refined designed to suit all Wisnetworks enterprise class AP equipments. A single controller can centrally supervise and manage the WiFi networks and multiple, distributed APs could be taken care and work in a more effective way.




No special training is required to operate the controller system. The main parameters of one/multi-WU\N networks is available on the dashboard. Simple design would also help to easily realize the real-time status monitoring and customized





Using the intelligent centrally management between Ac and AP can quickly synchronize wireless configuration into each AP to complete a unified construction of the wireless network. configurations.

Unlimited AP Numbers

Unlimited AP numbers controlled by WisCloud controller would provide best experience for customers to plan and expand the WU\N networks.







One Wiscloud Controller Supports for Unlimited AP Numbers



Feature

Enterprise Level Radio Chipset

The high speed 1.2GHz Qualcomm CPU and 512MB DDR makes WisCloud access points much powerful to provide a stable connectivity and multifunctional wireless networks.

Various APs Optional


meet different requirements from customers, we provide corresponding AP with different feature parameters including frequency, speed, tx power and installation method etc.

Supports Fat AP & Fit AP Mode

All wireless network solution is completed by integrated fit ap and controller. While fat AP is quite perfect for users who owns a few APs.working with standalone. Fit AP is more suitable for enterprise / ISP level wireless network and massive deployment.

Support for Standard 802.3af/at

WisCloud Access Point is able to be supplied power 802.3af PoE technology and make it more flexible to deploy the device in indoor ceiling environment.











Model	WCAP-Lite	WCAP-AX	WCAP-AX-Plus	WCAP-AX-Pro
Frequency	2,4GHz	2,4GHz & 5GHz	2,4GHz & 5GHz	2,4GHz & 5GHz
2.4GHz speed	300Mbps	574Mbps	574Mbps	574Mbps
2.4GHz MIMO	2*2	2*2	2*2	2*2
5GHz speed	×	1201Mbps	2402Mbps	4804Mbps
5GHz MIMO	×	2*2	2*2	4*4
PoE	802.3af/at	802.3af/at	802.3af/at	802.3af/at
DC	×	×	V	V
Ceiling Mount	$\sqrt{}$	√	V	V
Tx power	23dBm	27dBm	27dBm	2.4GHz (27dBm),5GHz (30dBm)
Distance	100m	150m	150m	150m



Specifications

Physical Characteristics				
Processor	Qualcomm			
Flash / Memory	512MB DDR, 32MB Flash			
LAN Port	1*10/100/1000M Gigabit			
Button	Reset			
Power	802.3af			
Max Power Consumption	18W			
Working Temperature	-10C ∽60C			
Working Humidity	0%∽95% non-condensing			
Mounting	Ceiling Mount/Wall Mount			
Wireless Characteristics				
Wi-Fi Standard	802.11 ax			
Frequency	2.4GHz&5GHz MU-MIMO			
Speed	2976Mbps			
Max Tx Power	23dBm			
Antenna	3dBi Dual Omni			
Multi-SSID	up to 8 SSID Per Radio			
Wireless Security	WEP, WPA-PSK, WPA-Enterprise (WRA/WPA2, TKP/AES)			
Concurrent Clients	150+			
Coverage Range	150m			
Advanced Characteristics				
Mode	FatAP/Fit AP			
VLAN	802.1q			
Guest Policy	Web Portal/Password			
MAC Filter	Blacklist			
User QoS	Speed Limit by User Group			
Wireless Uplink	Supported			